

STAINLESS VALVES

Street
SERIES

Engine Pro Performance Stainless Valves feature superior design engineering and enhanced product features. Our valves are manufactured to exacting standards and from only the highest quality materials.

- Undercut Stem
- Fully Machined
- Hardened Tip
- One Piece Forging
- Stainless Steel Alloy
- Hard Chrome Plated Stem



PART #	TYPE	HEAD DIAMETER	STEM DIAMETER	INSTALLED HEIGHT	OVERALL LENGTH	TIP LENGTH
CHEVROLET SMALL BLOCK						
01-1000	EXH	1.500	11/32"	STOCK	4.910	.250
01-1001	EXH	1.600	11/32"	STOCK	4.910	.250
01-1001.100	EXH	1.600	11/32"	+100	5.010	.250
01-1002	INT	1.940	11/32"	STOCK	4.910	.250
01-1003	INT	2.020	11/32"	STOCK	4.910	.250
01-1003.100	INT	2.020	11/32"	+100	5.010	.250
01-1007	INT	2.055	11/32"	STOCK	4.910	.250
01-1007.100	INT	2.055	11/32"	+100	5.010	.250
01-1008	INT	2.080	11/32"	STOCK	4.910	.250
01-1008.100	INT	2.080	11/32"	+100	5.010	.250
CHEVROLET BIG BLOCK						
01-1011	EXH	1.720	3/8"	STOCK	5.352	.250
01-1004	EXH	1.880	3/8"	STOCK	5.352	.250
01-1010	INT	2.065	3/8"	STOCK	5.228	.250
01-1005	INT	2.190	3/8"	STOCK	5.228	.250
FORD SMALL BLOCK						
01-1102	EXH	1.460	11/32"	STOCK	5.070	.395
01-1101	INT	1.780	11/32"	STOCK	5.070	.395

STAINLESS VALVES

Competition
SERIES

Out perform the competition with these superior stainless one-piece valves. Our Competition Series Valves feature 21-4N stainless alloy, hard wafer tip, chromed stem, full undercut and swirl polished for optimum flow.

- High Strength Stainless Alloy (21-4N)
- Swirl Polished for Improved Flow Characteristics



PART #	TYPE	HEAD DIAMETER	STEM DIAMETER	INSTALLED HEIGHT	OVERALL LENGTH	TIP LENGTH
CHEVROLET SMALL BLOCK						
01-2000	EXH	1.500	11/32"	STOCK	4.910	.250
01-2001	EXH	1.600	11/32"	STOCK	4.910	.250
01-2001.100	EXH	1.600	11/32"	+100	5.010	.250
01-2002	INT	1.940	11/32"	STOCK	4.910	.250
01-2003	INT	2.020	11/32"	STOCK	4.910	.250
01-2003.100	INT	2.020	11/32"	+100	5.010	.250
01-2007.100	INT	2.055	11/32"	+100	5.010	.250
01-2008.100	INT	2.080	11/32"	+100	5.010	.250
CHEVROLET BIG BLOCK						
01-2004	EXH	1.880	3/8"	STOCK	5.352	.250
01-2004.100	EXH	1.880	11/32"	+100	5.452	.250
01-2005	INT	2.190	3/8"	STOCK	5.228	.250
01-2012.250	INT	2.250	11/32"	+250	5.478	.250
01-2013.250	INT	2.300	11/32"	+250	5.478	.250
MITSUBISHI ECLIPSE 2.0L dohc 16 valve (4G63 - 4G63T) 1990-2000						
01-2103	EXH	30.5mm	6.55mm	STOCK	109.7mm	3.8mm
01-2104	EXH	31.5mm	6.55mm	STOCK	109.7mm	3.8mm
01-2101	INT	34mm	6.57mm	STOCK	109.7mm	3.8mm
01-2102	INT	35mm	6.57mm	STOCK	109.7mm	3.8mm